CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION OFFICE OF THE STATE FIRE MARSHAL

FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM

LISTING SERVICE

LISTING No. 7167-1273:113 Page 1 of 1

CATEGORY: Control Unit (Household)

LISTEE: Digital Security Control, 95 Bridgeland Avenue, Toronto, Ontario, Canada M6A 1Y7*

Contact: Dan Nita (905) 760-3000 FAX (905) 760-3020

DESIGN: Models PC4010, PC4010CF, PC4020, PC4020CF, P-864, P-864CF, P-16128, and

16128CFcombination fire and burglary fire alarm control units. Refer to listee's data sheet

Control Unit

Keypads

Keypads

Keypads

Keypads

for additional detailed product description and operational considerations. System

components:

PC4010, PC4020, P-864, P-16128

LCD-4500, LCD-4500T

LCD-4501, LCD-4501T, LCD-4510 RPS400, RPS-400T, LCD400T, PRS400F LCD4521T, PRS400FT, LCD4520, LCD4521

PC4108, P4108, PC4116, P4116

Zone Expander PC4204, P4204 Power Supply/Relay Module

Output Module PC4216, P4216

PC4001C, P4002C, P4003C Enclosure

RS232 Interface Module PC4400

PC4700, P4700, PC4701, P4701 Fire Module

PC4612A, P4612A Zone Annunciators

RATING: 120 VAC, 12 VDC

In accordance with listee's printed installation instructions, applicable codes & ordinances and **INSTALLATION:**

> in a manner acceptable to the authority having jurisdiction. The system must have the secondary power supply capable of operating the system for at least 24 hours (battery standby) in the normal condition and followed by not less than 4 minutes of alarm as required

by code.

MARKING: Listee's name (DSC) or "Partner", model number, electrical rating and UL label.

Listed as combination household fire and burglary alarm control units for use with APPROVAL:

separately listed compatible initiating and indicating devices.

This control unit can generate a distinctive three-pulse Temporal Pattern Fire Alarm Evacuation Signal (for total evacuation) in accordance with NFPA 72, 1996 Edition. Refer

to listee's Installation Instruction Manual for details.

NOTE: Burglary and other non-fire functions were not examined.

*Rev. 06-15-2002



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other suitable information sources.

JUNE 22, 2004 Date Issued: Listing Expires June 30, 2005

DIANE K. AREND, Senior Deputy Authorized By:

Program Manager